

# Material Safety Data Sheet

24 Hour Assistance:  
1-847-367-7700  
Rust-Oleum Corp.  
www.rustoleum.com

## Section 1 - Chemical Product / Company Information

Product Name: Rust-Oleum Stops Rust Aluminum Primer  
Revision Date: 05/06/2003  
Identification Number: 8781402, 8781504  
Product Use/Class: Primer/Water Based Acrylic  
Supplier: Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA  
Manufacturer: Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA  
Preparer: Department, Regulatory

## Section 2 - Composition / Information On Ingredients

Chemical Name	CAS Number	Weight % Less Than	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Calcium Carbonate	1317-65-3	15.0	10 mg/m3	N.E.	15 mg/m3	N.E.
Titanium Dioxide	13463-67-7	10.0	10 mg/m3	N.E.	10 mg/m3	N.E.
Propylene Glycol	57-55-6	5.0	N.E.	N.E.	N.E.	N.E.
Diethylene Glycol Monomethyl Ether	111-77-3	5.0	N.E.	N.E.	N.E.	N.E.
Zinc Phosphate	7779-90-0	5.0	N.E.	N.E.	N.E.	N.E.
Dibutyl Phthalate	84-74-2	5.0	5 mg/m3	N.E.	5 mg/m3	N.E.
Propylene Glycol Monobutyl Ether	5131-66-8	5.0	N.E.	N.E.	N.E.	N.E.
Ethylene Glycol Mono-ethyl-hexyl Ether	1559-35-9	5.0	N.E.	N.E.	N.E.	N.E.

## Section 3 - Hazards Identification

\*\*\* Emergency Overview \*\*\*: Use ventilation necessary to keep exposures below recommended exposure limits, if any.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: Substance may cause slight skin irritation.

Effects Of Overexposure - Inhalation: Low hazard for usual industrial handling or commercial handling by trained personnel.

Effects Of Overexposure - Ingestion: Substance may be harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: Contains: Propylene Glycol. Human systemic effects by ingestion: general anesthesia, convulsions, changes in surface EEG. Effects of overexposure may include irritation of the nose and throat, irritation of the digestive tract and signs of nervous system depression (e.g., headache, drowsiness, loss of coordination and fatigue).

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Eye Contact

## **Section 4 - First Aid Measures**

First Aid - Eye Contact: Hold eyelids apart and flush with plenty of water for at least 15 minutes. Get medical attention.

First Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

First Aid - Ingestion: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

## **Section 5 - Fire Fighting Measures**

Flash Point: >212 F  
(Setaflash)

LOWER EXPLOSIVE LIMIT: 2.6 %  
UPPER EXPLOSIVE LIMIT : 12.6 %

Extinguishing Media: Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

Special Firefighting Procedures: Water may be used to cool closed containers to prevent buildup of steam.

## **Section 6 - Accidental Release Measures**

Steps To Be Taken If Material Is Released Or Spilled: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

## **Section 7 - Handling And Storage**

Handling: Wash thoroughly after handling. Wash hands before eating. Avoid contact with eyes.

Storage: Keep from freezing. Keep container closed when not in use.

## **Section 8 - Exposure Controls / Personal Protection**

Engineering Controls: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other protective equipment: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking.

## Section 9 - Physical And Chemical Properties

Boiling Range:	369 - 369 F	Vapor Density:	Heavier than air
Odor:	Ammonia Like	Odor Threshold:	ND
Appearance:	Liquid	Evaporation Rate:	Slower than Ether
Solubility in H <sub>2</sub> O:	Soluble		
Freeze Point:	ND	Specific Gravity:	1.0230
Vapor Pressure:		PH:	NE
Physical State:	Liquid		

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

Conditions To Avoid: Avoid contact with strong acid and strong bases.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition it emits acrid smoke and irritating fumes. By open flame, carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

## Section 11 - Toxicological Information

Product LD50: ND

Product LC50: ND

<b><u>Chemical Name</u></b>	<b><u>LD50</u></b>	<b><u>LC50</u></b>
Calcium Carbonate	N.D.	N.D.
Titanium Dioxide	>7500 mg/kg	N.D.
Propylene Glycol	20000 mg/kg (ORAL, RAT)	N.D.
Diethylene Glycol Monomethyl Ether	7000 mg/kg (ORAL, RAT)	N.D.
Zinc Phosphate	N.D.	N.D.
Dibutyl Phthalate	8000 mg/kg (ORAL, RAT)	N.D.
Propylene Glycol Monobutyl Ether	2200 mg/kg	N.D.
Ethylene Glycol Mono-ethyl-hexyl Ether	4674 mg/kg (ORAL, RAT)	N.D.

## Section 12 - Ecological Information

Ecological Information: Product is a mixture of listed components.

## Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.

## Section 14 - Transportation Information

DOT Proper Shipping Name:	Paint	Packing Group:	---
DOT Technical Name:	---	Hazard Subclass:	Not Regulated
DOT Hazard Class:	---	Resp. Guide Page:	---
DOT UN/NA Number:	UN 1263		

## Section 15 - Regulatory Information

### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD

### SARA Section 313:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<b><u>Chemical Name</u></b>	<b><u>CAS Number</u></b>
Diethylene Glycol Monomethyl Ether	111-77-3
Zinc Phosphate	7779-90-0
Dibutyl Phthalate	84-74-2
Ethylene Glycol Mono-ethyl-hexyl Ether	1559-35-9

### Toxic Substances Control Act:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None known

### U.S. State Regulations: As follows -

### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

**Chemical Name**

Water  
Modified Acrylic Copolymer

**CAS Number**

7732-18-5  
PROPRIETARY

**Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%.

**Chemical Name**

Water  
Modified Acrylic Copolymer

**CAS Number**

7732-18-5  
PROPRIETARY

**California Proposition 65:**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

**Chemical Name**

Microcrystalline Silica  
Lead Compounds  
Cadmium Compounds  
Ethylene Oxide  
Arsenic Compounds

**CAS Number**

14808-60-7  
NOT SPECIFIED  
NOT SPECIFIED  
75-21-8  
NOT SPECIFIED

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

**Chemical Name**

Lead Compounds  
Cadmium Compounds  
Ethylene Oxide  
Arsenic Compounds  
Ethylene Glycol Monoethyl Ether

**CAS Number**

NOT SPECIFIED  
NOT SPECIFIED  
75-21-8  
NOT SPECIFIED  
110-80-5

**International Regulations: As follows -****CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** D2B

**Section 16 - Other Information****HMIS Ratings:**

Health: 1

Flammability: 0

Reactivity: 0

Personal Protection: X

**VOLATILE ORGANIC COMPOUNDS, g/l:** <250

**REASON FOR REVISION:**

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.